

DEI

Demineralised Water

DEI is demineralised water supplied by Electrolube to enable small to medium users the ability to give a final “polish” to circuit boards and assemblies which have been cleaned using Electrolube Safewash and rinsed in tap water.

| <u>Description</u> | <u>Packaging</u> | <u>Order Code</u> | <u>Shelf Life</u> |
|---------------------|--|-------------------|------------------------|
| Demineralised Water | 1 litre plastic container 5 litre plastic container | DEI01L DEI05L | 36 Months 36 Months |

Directions for Use

DEI is an ideal product to be used in conjunction with Electrolube’s TSB. TSB is an empty, refillable trigger spray with adjustable nozzle.

It is not advisable to use DEI in a container and immerse the assembly or board, as DEI may quickly become contaminated with salts from tap water or even un-rinsed residues from the initial cleaning process.

Hold the PCB or assembly at approx. 45°. Spray DEI generously onto the assembly and allow to run down the board. The PCB may be quickly dried using Electrolube Airduster (EAD).

Revision 1: Apr 2014

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
Ashby de la Zouch,
Leicestershire LE65 1JR
T +44 (0)1530 419 600
F +44 (0)1530 416 640
BS EN ISO 9001:2008
Certificate No. FM 32082